

LED 내압 방폭등

Explosion Proof LED Lighting Fixture (Exd IIC)

Top rate energy saving
Excellent luminous efficiency
Consistent color rendering
Light weight
Effortless installation
Quality waterproof part



LED Exd IIC T6 IP-66 For Zone 1




PRODUCT CONTENTS

Model No.	LUNA-Exd-L100		
Power	70W	80W	100W
Replaced	MH 250W	MH 300W	MH 400W
Energy saving	85%	85%	85%
Luminous Efficiency	150lm/W±10%	149lm/W±10%	140lm/W±10%
Total luminous flux	10,500lm±10%	11,920lm±10%	14,000lm±10%
Type	External, SMPS		
Protection	Exd IIC T6 IP66		
Ambient Temp.	-20~+40°C		
Weight	6Kg±5%		
Warranty	3 Years		
Rated Voltage	AC 100~240V		
Frequency	50HZ ~ 60HZ		
Power factor	MIN, 90%		
CCT	5,000K±10%		
CRI	85±5%		
Beam angle	120°		
Descriptions	Materials		
Body & Cover	Cast Aluminum Alloy		
Front cover	Heat resistant hard glass		
SMPS	Constant Current		
ACC	SUS		

PHOTOMETRIC DATA

Photometric data-120



CERTIFICATION



Korean Women
Entrepreneurs
Association



LED Exd IIC T6 IP-66 For Zone 1

PRODUCT SPECIFICATION

